



FITTING INSTRUCTIONS

MDF 3D Panels

UNLOADING & MANUAL HANDLING

Unpack all of the panels and check that there are no breakages or damage.

STORING

The Product should be stored in a closed and dry space, in temperatures between 5°-25° degrees Celsius. Tiles should be unpacked and laid on an even surface 48h before creating fitting.

PREPARATION

The wall should be straight, solid, consistent and clear from loose elements, preferably sealed with PVA.

FITTING

MDF panels can be glued, handled or screwed through the panel edge groove base flap into plumb and level wooden battens, or bonded directly onto to flat, plumb, sound and smooth walls or ceilings. If the installation sub-surface is uneven, then you need to install an appropriate timber batten frame system to the wall or ceiling before fixing; this will ensure that you then have a level batten frame to apply the panels to.

If gluing panels to the wall, ceiling or framework then you should apply high-tack adhesive into the back of the panel and angle it into the wall. You can then fit the next panel tongue into the groove of the previously installed panel and fix in the same manner as the first panel.

Finish the installation of the panels by measuring and cutting the last one panel to size. MDF panels should be carefully cut using a fine-tooth blade hand-saw, ensuring that the decorative side is face-up. Gloves and eye protection should be worn when cutting the panels to minimize the risk of injury.

When fixing any accessories or heavy items to the MDF panel surface, ensure that the screws used to fix the item locate securely into the wall or battens and not just into the as MDF material.

CUTTING

Measure and designate a line along which the panel must be cut.

Put it on a soft surface (blanket, foam pad) upside down.

Mark the cutting line.

Cut the panel using a saw or fretsaw with fine blade teeth.

MAINTENANCE

Sweep with dry cloth or vacuum the panels regularly to remove all dust. General household cleaners may be too aggressive and are likely to damage the sealants and finishes applied.

RECOMMENDED ACCESSORIES

Glue gun / PU Glue / Saw / Measure tape / Knife/ Spirit level / Pencil

DISPOSAL

Dispose of in compliance with all local and national regulations. Waste of wood products are normally classified as non-hazardous, but should not be co-disposed with municipal waste.

DISCLAIMER

We reserve the right to amend the details contained within this document without prior notice. Material can have minor manufacturing characteristics present such as colour fluctuation and minor surface particle or imperfections. These are normal visual elements for this type of product and if present are not grounds for complaint and are not aspects covered by the product warranty. Final results largely depend on the tiler skills and his experience with art tiles fitting.